

<b>SPECIFICA TECNICA</b>	
TC92535 MONTANTE SINTETICO PER VETRINI metodo con Isoparaffina	
REV. 2 DEL 29/09/2022	Metodo controllo MC92535

Nome prodotto	<b>MONTANTE SINTETICO PER VETRINI metodo con Isoparaffina</b>	
Codice prodotto	<b>TC92535</b>	
Composizione	<b>Miscela di resina acrilica termoplastica in solvente isoparaffinico</b>	
<b>SPECIFICHE TECNICHE</b>		
<b>Aspetto</b>	Liquido incolore	
<b>Viscosità</b>	970 - 1030 cP	
<b>Indice di rifrazione</b>	1,430 - 1,450	
<b>Idoneità all'uso</b>	Montante sintetico universale	
<b>Scadenza</b>	4 anni dalla produzione in confezione integra	
<b>DOCUMENTO EMESSO A MEZZO COMPUTER E PERTANTO NON FIRMATO</b>		

<b>TECHNICAL DATA SHEET</b>	
TC92535 SYNTHETIC MOUNTING FOR SLIDES method with isoparaffin	
REV. 2 - 29/09/2022	Control method MC92535

Product name	<b>SYNTHETIC MOUNTING FOR SLIDES method with isoparaffin</b>	
Product Code	<b>TC92535</b>	
Composition	<b>Mixture of thermoplastic acrylic resin in isoparaffinic solvent</b>	
<b>TECHNICAL SPECIFICATIONS</b>		
<b>Appearance</b>	Colorless liquid	
<b>Viscosity</b>	970 - 1030 cP	
<b>Refractive index</b>	1,430 - 1,450	
<b>Suitability for use</b>	Syntetic mounting for slides	
<b>Expiry date</b>	4 years from production in tightly closed bottle	
THIS DOCUMENT HAS BEEN MADE BY ELECTRONIC DATA PROCESSING AND THEREFORE NOT SIGNED		