

SPECIFICA TECNICA	
TC43330 ACIDO SOLFORICO 30% p/p	
REV. 02 DEL 14/04/205	Metodo controllo MC230

Nome prodotto	ACIDO SOLFORICO 30% p/p	
Codice prodotto	TC43330	
SPECIFICHE TECNICHE		
Aspetto	Liquido limpido incolore	TC MC230
Titolo	29,5 – 30,5 % p/p	TC MC230
Anidride Solforosa (SO ₂)	≤ 1 ppm	SPEC. FORN.
Cloruri (Cl)	≤ 0,01 ppm	SPEC. FORN.
Azoto tot. (N)	≤ 1,0 ppm	SPEC. FORN.
Ferro (Fe)	≤ 20 ppm	SPEC. FORN.
Arsenico (As)	≤ 0,01 ppm	SPEC. FORN.
Piombo (Pb)	≤ 0,05 ppm	SPEC. FORN.
Rame (Cu)	≤ 0,05 ppm	SPEC. FORN.
Metalli pesanti (Cr+V+Ni+Mn)	≤ 2 ppm	SPEC. FORN.
Sostanze riducenti KMnO ₄ (O ₂)	≤ 2 ppm	SPEC. FORN.
Residuo di calcinazione	≤ 50 ppm	SPEC. FORN.
DOCUMENTO EMESSO A MEZZO COMPUTER E PERTANTO NON FIRMATO		

TECHNICAL DATA SHEET	
TC43330 SULFURIC ACID 30% w/w	
REV. 02 - 14/04/2005	Control Method MC230

Product name	SULFURIC ACID 30% w/w	
Product code	TC43330	
TECHNICAL SPECIFICATIONS		
Appearance	Clear colorless liquid	TC MC230
Assay	29.5 - 30.5 % w/w	TC MC230
Sulfur Dioxide (SO ₂)	≤ 1 ppm	SPEC. SUPP.
Chlorides (Cl ⁻)	≤ 0.01 ppm	SPEC. SUPP.
Total Nitrogen	≤ 1.0 ppm	SPEC. SUPP.
Iron (Fe)	≤ 20 ppm	SPEC. SUPP.
Arsenic (As)	≤ 0.01 ppm	SPEC. SUPP.
Lead (Pb)	≤ 0.05 ppm	SPEC. SUPP.
Copper (Cu)	≤ 0.05 ppm	SPEC. SUPP.
Heavy metals (Cr+V+Ni+Mn)	≤ 2 ppm	SPEC. SUPP.
Reducing substances KMnO ₄ (O ₂)	≤ 2 ppm	SPEC. SUPP.
Calcination residue	≤ 50 ppm	SPEC. SUPP.
DOCUMENT ISSUED BY COMPUTER AND THEREFORE NOT SIGNED		