

SPECIFICA TECNICA	
TC91300 CONDUCIBILITA' 3000 $\pm$ 30 uS/cm a 25°C	
REV. 02 DEL 12/10/2004	Metodo controllo MC587

Nome prodotto	CONDUCIBILITA' 3000 ± 30 uS/cm a 25°C	
Codice prodotto	TC91300	
SPECIFICHE TECNICHE		
Aspetto	Liquido limpido incolore	
Conducibilità (25°C)	2,97 – 3,03	
Corrispondenza Temperatura (°C) / mS/cm		
16	2,41	
17	2,48	
18	2,54	
19	2,61	
20	2,67	
21	2,74	
22	2,80	
23	2,87	
24	2,93	
25	3,00	
26	3,06	
27	3,12	
28	3,17	
29	3,23	
30	3,29	
31	3,35	
32	3,41	
33	3,46	
34	3,52	
Il valore riscontrato è riferibile tramite una catena di confronti allo Standard Reference Material 999c del National Institute of Standards and Technology (NIST – USA – www.nist.gov)		
DOCUMENTO EMESSO A MEZZO COMPUTER E PERTANTO NON FIRMATO		

TECHNICAL DATA SHEET	
TC91300 CONDUCTIVITY solution 3000 $\mu\text{S}/\text{cm}$ at 25°C	
REV. 02 - 12/10/2004	Control Method MC587

Product name	CONDUCTIVITY solution 3000 $\mu\text{S}/\text{cm}$ at 25°C
Product code	TC91300
TECHNICAL SPECIFICATIONS	
Appearance	Clear colorless liquid
Conductivity (25°C)	2.97 - 3.03
Correspondence Temperature (°C) / mS/cm	
16	2,41
17	2,48
18	2,54
19	2,61
20	2,67
21	2,74
22	2,80
23	2,87
24	2,93
25	3,00
26	3,06
27	3,12
28	3,17
29	3,23
30	3,29
31	3,35
32	3,41
33	3,46
34	3,52
The value found can be traced back through a chain of comparisons to the Standard Reference Material 999c of the National Institute of Standards and Technology (NIST - USA - www.nist.gov)	
DOCUMENT ISSUED BY COMPUTER AND THEREFORE NOT SIGNED	